CTOLIGHTING

LUNAR PENDANT MEDIUM

FINISH

bronze with satin brass and bronze oval chain

DIMENSIONS (body of fixture)

600 x 400 x 600 mm (w x d x h)

WEIGHT

8kg (17.6lbs)

please ensure ceiling structure is strong enough to support the weight of the light

OVERALL DROP

minimum 675 mm supplied with 1000mm flex and chain as standard (adjustable on site)

ILLUMINATION

220-240v - 1 x E27 - 12.5w PAR 30 2700k LED ONLY 110-130v - 1 x E26 - 12.5w PAR 30 2700k LED ONLY

DIMMING

dimmable bulb required trailing edge dimmable / phase cut (rotary dimmer) - standard DALI option available (220-240v only)

CEILING ROSE / PLATE

round ceiling rose - \emptyset 116 x 25 mm (dia x h)

CERTIFICATION









E492308

VIEW ON WEBSITE










mounting plate dimensions



^{*}Diagrams are not to scale.

CTOLIGHTING

LUNAR PENDANT MEDIUM - DALI-A

FINISH

bronze with satin brass and bronze oval chain

DIMENSIONS (body of fixture)

600 x 400 x 600 mm (w x d x h)

WEIGHT

8kg (17.6lbs)

please ensure ceiling structure is strong enough to support the weight of the light

OVERALL DROP

minimum 675 mm supplied with 1000mm flex and chain as standard (adjustable on site)

ILLUMINATION

 $220-240v - 1 \times E27 - 12.5w$ PAR 30 2700k LED ONLY DALI converter to be installed in the ceiling rose.

DIMMING

dimmable bulb required DALI compatible

CEILING ROSE / PLATE

round ceiling rose - ø 116 x 25 mm (dia x h)


CERTIFICATION






VIEW ON WEBSITE










mounting plate dimensions



^{*}Diagrams are not to scale.



LUNAR PENDANT MEDIUM

LUNAR PENDANT MEDIUM

SKU NUMBER	FINISH DESCRIPTION	VOLTAGE
LUNPEMBZSB-240	bronze with satin brass and bronze oval chain	220 - 240V
LUNPEMBZSB-110	bronze with satin brass and bronze oval chain	110 - 130v

LUNAR PENDANT MEDIUM - DALI-A

SKU NUMBER	FINISH DESCRIPTION	TYPE OF DALI	VOLTAGE
LUNPEMBZSB-DALIA-240	bronze with satin brass and bronze oval chain	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted in the existent ceiling/wall rose	220 - 240V