CTOLIGHTING

PENDULUM PENDANT

FINISH

bronze with smoked glass satin brass with smoked glass

DIMENSIONS (body of fixture)

 $320 \times 150 \times 525 \text{ mm} (w \times d \times h)$

WEIGHT

8kg (17.6lbs)

please ensure ceiling structure is strong enough to support the weight of the light

OVERALL DROP

minimum 665 mm

supplied with 1000mm drop rod (12.7mm dia) as standard (adjustable on site)

ILLUMINATION

220-240v - integrated LED - 8w - 2700K

110-130v - integrated LED - 8w - 2700K

LED driver to be installed in the ceiling rose

drivers must be installed up to 20 meters from the body of the light

DIMMING

trailing edge dimmable / phase cut (rotary dimmer) - standard DALI option available (220-240v only) 0/1-10v (220-240v or 110-130v) - on request

CEILING ROSE / PLATE

round ceiling rose - ø 45 x 120 mm (dia x h)


CERTIFICATION







VIEW ON WEBSITE













mounting plate dimensions



North America junction box cover



^{*}Diagrams are not to scale.

CTOLIGHTING

PENDULUM PENDANT - DALI-A

FINISH

bronze with smoked glass satin brass with smoked glass

DIMENSIONS (body of fixture)

 $320 \times 150 \times 525 \text{ mm} (w \times d \times h)$

WEIGHT

8kg (17.6lbs)

please ensure ceiling structure is strong enough to support the weight of the light

OVERALL DROP

minimum 665 mm supplied with 1000mm drop rod (12.7mm dia) as standard (adjustable on site)

ILLUMINATION

integrated LED - 8w - 2700K DALI LED driver to be installed in the ceiling cavity drivers must be installed up to 20 meters from the body of the light

DIMMING

DALI compatible

CEILING ROSE / PLATE

round ceiling rose - ø 45 x 120 mm (dia x h)


CERTIFICATION







VIEW ON WEBSITE













mounting plate dimensions



LED driver dimensions



^{*}Diagrams are not to scale.

CTOLIGHTING

PENDULUM PENDANT - DALI-B

FINISH

bronze with smoked glass satin brass with smoked glass

DIMENSIONS (body of fixture)

 $320 \times 150 \times 525 \text{ mm} (w \times d \times h)$

WEIGHT

8kg (17.6lbs)

please ensure ceiling structure is strong enough to support the weight of the light

OVERALL DROP

minimum 580 mm supplied with 1000mm drop rod (12.7mm dia) as standard (adjustable on site)

ILLUMINATION

integrated LED - 8w - 2700K DALI LED driver to be installed in the ceiling rose

DIMMING

DALI compatible

CEILING ROSE / PLATE

round ceiling rose - ø 140 x 35 mm (dia x h)


CERTIFICATION







VIEW ON WEBSITE














*Diagrams are not to scale.



PENDULUM PENDANT

PENDULUM PENDANT

SKU NUMBER	FINISH DESCRIPTION	VOLTAGE
PENPEOBZSG-240	bronze with smoked glass	220 - 240V
PENPEOSBSG-240	satin brass with smoked glass	220 - 240V
PENPEOBZSG-110	bronze with smoked glass	110 - 130V
PENPEOSBSG-110	satin brass with smoked glass	110 - 130V

PENDULUM PENDANT - DALI-A

SKU NUMBER	FINISH DESCRIPTION	TYPE OF DALI	VOLTAGE
PENPEOBZSG-DALIA-240	bronze with smoked glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall cavity	220 - 240V
PENPEOSBSG-DALIA-240	satin brass with smoked glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall cavity	220 - 240V

PENDULUM PENDANT - DALI-B

SKU NUMBER	FINISH DESCRIPTION	TYPE OF DALI	VOLTAGE
PENPEOBZSG-DALIB-240	bronze with smoked glass	DALI B included - The light will feature a deeper ceiling/wall rose. For use when there is no space in the existing ceiling/wall cavity	220 - 240V
PENPEOSBSG-DALIB-240	satin brass with smoked glass	DALI B included - The light will feature a deeper ceiling/wall rose. For use when there is no space in the existing ceiling/wall cavity	220 - 240V